SV-EXTCAM HIGH RESOLUTION MICRO EXTERIOR CAMERA



The Micro Exterior camera is ideal for tight spots and side views such as on the underside of mirrors or on fenders. The unique slim cable connection fits through tight panel gaps, increasing versatility during installation and retains an OEM look. The Micro Exterior camera can be rotated 360°, allowing one model to be used for both left and right side applications.

IMAGE SENSOR

1/3" CMOS PC1089K

RESOLUTION 728 × 488

SYNC SYSTEM Internal

SIGNAL-TO-NOISE RATIO >48dB

TV LINES 500

6

FOCAL LENGTH 2.8mm (3.6mm optional)

FIELD OF VIEW

150° (2.8 mm) INFRARED ILLUMINATORS

MINIMUM ILLUMINATION O lux (with IRs)

ELECTRONIC SHUTTER 1/60 ~ 1/100,000 sec

AUTO ADJUSTMENTS White Balance, Auto Gain, Back Light Compensation

VIDEO OUTPUT 1.0Vp-p, 75Ω

AUDIO

Integrated microphone IP RATING IP69K

POWER REQUIREMENT

OPERATING TEMPERATURE

-22° F ~ 158° F (-30°C ~ 70°C) (RH 95% max.)

DIMENSIONS (W × H × D) 2.26 × 1.66 × 2.6 in. (57.4 × 42.2 × 66.0 mm) **CERTIFICATIONS**


MIL-STD-810


PART NUMBER

SV-EXTCAM-BLACK (black housing) SV-EXTCAM-WHITE (white housing)

FEATURES

- Wide 150° viewing angle
- Clear 500 TV lines resolution
- Extremely rugged IP69K rating
- IR illuminators for clear images in low light
- Available in both white and black to match vehicle exterior





6100 W. Sam Houston Pkwy. N. Houston , TX 77041



800.880.8855 www.safetyvision.com