

LED7-TS MONITOR

7" TOUCHSCREEN MONITOR



The LED7-TS single-view monitor supports up to 4 HD channels with 1080p max resolution for crystal-clear picture quality. The 7-inch touch-screen display provides full-screen views of each camera and includes up to 4 triggers to automatically switch to a camera's view. Equipped with parking lines to assist when maneuvering backwards, the LED7-TS also includes a built-in speaker so drivers can both see and hear activity within the camera's range.

LCD SIZE

7 in.

RESOLUTION

1024 × 3 (RGB) × 600

DIMENSIONS (W × H × D)

7.99 × 4.41 × 1.10in (203 × 112 × 28mm)

POWER INPUTS

10 ~ 32V DC

DOT PITCH

0.15(H) × 0.1444 (V)

CONTRAST

800:1

BRIGHTNESS

600 cd/m²

VIEWING ANGLE

Up: 85° / Down: 85° / Right: 85° / Left: 85°

AUDIO

Yes; integrated speaker

AUDIO OUTPUT

1W

DIMMER

Manual/Automatic (selectable)

OPERATING TEMPERATURE

-4° F ~ 158° F (-20°C ~ 70°C) RH 90%

STORAGE TEMPERATURE

-22° F ~ 176° F (-30°C ~ 80°C) RH 90%

POWER CONSUMPTION

~8W

VIDEO INPUTS

3 / 4 inputs (13 / 22pin), 1 HDMI

AUDIO INPUTS

3 / 4 inputs (13 / 22pin)

VIDEO OUTPUTS

0

AUDIO OUTPUTS

0

TRIGGER SIGNAL

3 / 4 trigger wires (13 / 22pin)

ANTI-VIBRATION

3 g (Center mount bracket) / 7 g (U-support bracket)

WEIGHT

1.6lb (7.3kg)

PART NUMBER

SV-LED7-TS

FEATURES

- 7-inch touch-screen display
- 1080p HD max resolution
- 4 camera inputs with automatic trigger
- Built-in speaker